

	Description	Unit	
<b>Capacity</b>	Table Area (ground)	mm	500 x 200
	Table Movements (longitudinal/cross)	mm	530 x 230
	Max. grinding height between table and new wheel (Ø 205)	mm	302.5
	Standard magnetic chuck	mm	450 x 200
	Table load capacity approx.	kg	120 (incl. Chuck) 1 x 17
<b>Table</b>	T Slots	(No. x W)	1 x 17
	Max Table feed, hydraulic, continuously adjustable, m/min	m/min	1. ~ 20
<b>Cross Feed</b>	Intermittent feed	mm	0.4 – 8
	Continuous feed	mm/min	0-2000
	Electronic hand wheel graduations	µm	0.1 / 1 / 10 / 50
<b>Down Feed</b>	Automatic Down Feed	mm	0.0001 - 0.030
	Electronic hand wheel graduations	µm	0.1 / 1 / 10
	Rapid Positioning	mm/min	2000
<b>Grinding wheel</b>	Grinding Wheel - OD x width x bore	mm	205 x 6-25 x 31.75
	Rotational speed	rpm	100 - 3600
<b>Motors</b>	Grinding spindle	kW	2.2
	Hydraulic Pump	kW	0.75
	Vertical Feed (AC Servomotor)	kW	0.5
	Cross feed	kW	0.5
<b>Power Supply</b>	Operating voltage/frequency	v/Hz	400 / 50
	Connected load, approx.	kVA	15
<b>Floor Space</b>	Length x Depth x Height, approx.	mm	2270 x 2780 x 2090
<b>Weight</b>	Net weight without accessories, approx.	kg	2100